



**S M I T H**™

**SMITH LINK**

Smith Electric Vehicles Telemetry Platform

The logo consists of a dark grey rounded rectangle containing the word "SMITH" in white, uppercase, sans-serif font. To its right is an orange rounded rectangle containing the word "LINK" in white, uppercase, sans-serif font. The two rectangles are separated by a diagonal white line.

SMITH

LINK

Smith Link is used to:

- Help Support department with vehicle diagnostics
- Support Product continual development
- Monitor vehicle performance

The logo for Smith-Link, featuring the word "SMITH" in white capital letters on a dark grey background, and the word "LINK" in white capital letters on an orange background, separated by a diagonal line.

SMITH

LINK

## Key Facts:

- 2500 data points each second
- ~ 500 vehicles
- 1.8 billion data points per day

Design of the Smith-Link system is  
“on the frontier of today's application  
techniques” – [cio.com](http://cio.com)



**SMITH**


**LINK**



SMITH

LINK

Battery State of Charge




Battery Voltage



Battery Current



Battery Max. Temp



# SMITH LINK

SMITH LINK

DASHBOARD
PERFORMANCE
CARBON
SETTINGS

LIVE
 ROUTE
 HISTORY
 USAGE

SETTINGS
 ANALYSIS
 FAULTS
 SERVICE
 NOTES
 DEVICE ISSUE

DASHBOARD

State of Charge

31%

Voltage

314V

Current

-125A

Speed

80

FAULT
BATT WARN
DT OVERTEMP
REGEN ENABLED
ABS ACTIVE
VS STATE
MS STATUS
MS STATE

DRIVETRAIN

RPM (x1000)

10

Torque Command

-125A

Accelerator pedal	25%	●
Brake pedal	0%	●
Availability	100%	●
24V Battery	24V	●
MSVDCL	123	●
MSVDCB	132	●

**REVERSING**  
Motor

TEMPERATURES

- Battery 1°C
- Drivetrain 1°C
- Cab 1°C
- Inverter T1 1°C
- Inverter T2 1°C
- Inverter T3 1°C
- Inverter T4 1°C
- Motor T1 1°C
- Motor T2 1°C

SMITH

LINK





PERFORMANCE

Smith Link → Customer area → Performance report

PERFORMANCE REPORT

Performance Summary: 1st Jan 2012 - 14th Jan 2012	
Statistics	
Distance	41450 miles
% over 40mph	52%
Accelerator Peaks	42 per mile
Brake peaks	1767 per mile
NET Cumulative Energy Draw	57761kWh
Gross Cumulative Energy Draw	62086kWh
Total Regenerative Braking Energy	4325kWh
Regenerative Energy Per Mile	0.1kWh/mile
Regenerative Energy Ratio	7%
Efficiency	0.7176 miles/kWh 1.3935 kWh/mile
On time	1952:29:18
Drive time	1343:58:17
A/C Usage	289:03:27
Heater Usage	246:30:13
Carbon offset details (Estimated)	
Carbon cost for journey	3732.38Kg
Typical cost for journey using diesel truck	8708.71Kg
Carbon saving	4976.33Kg

Details
3rd Jan 2012
4th Jan 2012
6th Jan 2012
7th Jan 2012
9th Jan 2012
10th Jan 2012
12th Jan 2012
13th Jan 2012
14th Jan 2012
5th Jan 2012
11th Jan 2012
2nd Jan 2012
1st Jan 2012
8th Jan 2012

*Only days where a vehicle travelled 1 mile or more are shown in detail.*



**S M I T H**

**LINK**


# Practical Uses of Telemetry for Battery Diagnostics

SMITH

LINK

Battery State of Charge


[click to print or export](#)



SMITH

LINK


Battery Voltage [click to print or export](#)





SMITH

LINK


Battery Current [click to print or export](#)







ANY QUESTIONS?



## Security:

- Data transfer:
  - Truck transmissions: AMQP (2048 AES)
  - Server transmissions: SCP (2048 DES)
  - Web: SSL
- Data separation:
  - Access delegated to small subset of staff
  - Data given to partners is ammonised (under agreement with customers)



# SMITH LINK

